



**Builder's Best, Inc.**  
 201 Broiles Drive  
 Jacksonville, TX 75766  
 888-368-7233  
 fax: 800-259-8368  
 www.BuildersBest.com

# PRO VINYL HOSE



## PRODUCT SPECIFICATIONS

- Vinyl Tubing
- High tensile steel wire, wound helix
- Permanently heat-sealed, between layers of PVC
- Polyvinyl Chloride Fllm
- Pressure Rating Positive 4" WC max Negative 1" WC max
- Maximum Operating Air Velocity 3.1 5000 FPM
- Self Extinguishing
- Temperature Range -10°F to +120°F
- Bend radius one diameter
- Useful as bathroom fan venting
- Not approved for dryer venting
- 1" Pitch

## PART NUMBERS

Diameter	Length	Part#	Qty	Package
3"	5'	110046	12	bulk
	8'	110047	12	bulk
	20'	110048	5	ind box
4"	5'	110053	4	ind box
	5'	110111	12	bulk
	8'	110052	12	display label
	8'	110112	12	bulk
	20'	110059	5	ind box
With two plastic clamps	5'	110062	4	ind box
	4"	8'	110653	12

## LABELS



 **Made in the U.S.A.**

## WARRANTY

Manufacturer assumes no responsibility for failure due to improper installation. All specifications and designs are subject to change without notice and without incurring liability.

**WARRANTY EXCLUSION AND DISCLAIMER** Seller specifically excludes, and hereby disclaims any express representation or express warranty of any kind with respect to the goods ordered hereunder. All implied warranties, including without limitation merchantability or fitness for a particular purpose or arising from a course of dealing or usage or trade shall expire and cease 45 days after date of delivery. Seller shall not be liable to buyer or any third party for any special, secondary, incidental, or consequential damages however arising. Nothing in this provision shall invalidate or restrict any right or remedy otherwise available under state or federal law. Materials and specifications subject to change without notice.

Pro Vinyl Hose V1 11/07/14