

Builder's Best, Inc. 201 Broiles Drive Jacksonville, TX 75766 903-586-8283 www.BuildersBest.com sales@buildersbest.com

# WIRE HELIX ALUMINUM FOIL HOSE WMF651 SilverDuct<sup>™</sup> Long Lengths



#### DESCRIPTION

SilverDuct<sup>™</sup> is a wire helix hose constructed to meet the UL® 2158A label for clothes dryer transition duct. SilverDuct<sup>™</sup> has steel wire support and a multi-ply design of aluminum, polyester laminate and metalized polyester.

UL® 2158A only covers installations up to 8 feet. This long length version is constructed to meet the standard, but does not carry the UL® label.

#### PRODUCT FEATURES

- NOT labeled, but constructed to meet UL® 2158A
- Steel wire helix duct
- Multi-ply design of aluminum/polyester laminate and metalized polyester
- PRO performance level

## WARNINGS

- UL® 2158A approval only for installations of 8 feet or less
- Foil ducts crush easily and may contribute to lint build-up, creating a fire hazard.



- Foil duct is not recommended by Builder's Best as dryer venting
- Check your clothes dryer manufacturer manual as installation may invalidate warranties
- Check local building codes for appropriate use

# PART NUMBERS


| Dia. | Length | Each # | Qty | Case # | Package     |
|------|--------|--------|-----|--------|-------------|
| 4"   | 20'    | 11506  | 6   | 111506 | Display Box |
| 4"   | 25'    | 11504  | 5   | 111504 | Ind. Box    |
| 4"   | 50'    | 11505  | 4   | 111505 | Ind. Box    |

# Display Box



## AIRFLOW

Made in the U.S.A.



## PERFORMANCE DATA

Recommended Operating Pressure:

6" w.g. positive - all diameters Temperature Range: -20°F Flame Speed: less ti

Smoke Developed:

-20°F to +200°F less than 25 less than 50

Max Velocity: 5000 fpm Installation:

Connections shall be made per installation instructions outlined by the appliance manufacturer and UL® 2158A.

### WARRANTY

Complete warranty statement at buildersbest.com/warranty