



Builder's Best, Inc.
201 Broiles Drive
Jacksonville, TX 75766
888-368-7233
fax: 800-259-8368
www.BuildersBest.com

4" STANDARD VINYL HOSE



PRODUCT SPECIFICATIONS

- Vinyl Tubing
- High tensile steel wire, wound helix
- Permanently heat-sealed, between layers of PVC
- Polyvinyl Chloride Fllm
- Self Extinguishing
- Bend radius one diameter
- Useful as bathroom fan venting
- Not approved for dryer venting
- 1" Pitch

PART NUMBERS

Diameter	Length	Part#	Qty	Package
4"	5'	110566	12	bulk
	8'	110567	12	bulk
	8'	010559	72	bulk
	20'	110568	5	ind box
	50'	110569	4	ind box
	50'	010743	144	skid

PERFORMANCE DATA

- Recommended Operating Pressure
Positive: 4" WC max
Negative: 1" WC max
- Maximum Velocity 3.1 5000 FPM
- Temperature Range -10°F to +120°F

LABELS



WARRANTY

Manufacturer assumes no responsibility for failure due to improper installation. All specifications and designs are subject to change without notice and without incurring liability.

WARRANTY EXCLUSION AND DISCLAIMER Seller specifically excludes, and hereby disclaims any express representation or express warranty of any kind with respect to the goods ordered hereunder. All implied warranties, including without limitation merchantability or fitness for a particular purpose or arising from a course of dealing or usage or trade shall expire and cease 45 days after date of delivery. Seller shall not be liable to buyer or any third party for any special, secondary, incidental, or consequential damages however arising. Nothing in this provision shall invalidate or restrict any right or remedy otherwise available under state or federal law. Materials and specifications subject to change without notice.

4" Standard Vinyl Hose V1 11/19/14