


Builder's Best, Inc. 201 Broiles Drive Jacksonville, TX 75766 903-586-8283 sales@buildersbest.com BuildersBest.com

# Zero Periscope<sup>™</sup> 0-5"





### DESCRIPTION

The Zero Periscope<sup>™</sup> is a rigid aluminum clothes dryer duct which telescopes from 0" to 5". It is useful when outlets overlap or are very close.

### PRODUCT FEATURES

- Telescopes 0" to 5"
- Sections are not reversible
- 4" Draw band swiveling female collar for clothes dryer connection
- 4" Crimped swiveling snap-lock male fitting for wall connection


### PRODUCT SPECIFICATIONS

- 2" x 6" rigid aluminum
- Smooth interior decreases air friction
- Optional baffles help direct airflow in 3-5" situations

### PART NUMBERS

Dia.	Length	Note	Each #	Qty	Case #	Package	UPC
4"	0-5"	with baffle	10175	9	110175	Display Card	722048101753
4"	0-5"	no baffle	10144	9	110144	Bulk	722048101449
4"	0-5"	no baffle	10149	9	110149	Ind. Box	722048101494

#### 0-5" Periscope: Functional venting distance is 5".




Functional length 5" from center of dryer outlet to center of wall outlet  $\begin{array}{c} & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & &$ 



#### PERFORMANCE DATA AND AIRFLOW Pressure Rating:

Positive: 6" WC max Negative: 6" WC max Maximum velocity: 5,000 FPM Operating Temp. Range: -100°F to+ 430°F Flame Spread: 0 Smoke Developed: 0 INSTALLATION: Installation instructions included



Periscopes provide nearly the same airflow properties as one semi-rigid metal flexible pipe with two Close Elbows®.

### RECOMMENDATIONS

• The International Mechanical Code recommends rigid metal duct for dryer exhaust as well as in-wall exhaust. IMC 504.6.1 & 504.8-3

• Dryer manufacturers specify "Only rigid or flexible metal vent shall be used for exhausting. Do not use plastic or metal foil vent."

### PATENTS

US 5,653,631; 5,943,743; 6,035,495; 5,121,948; D.342,782 Canadian 2,062,123; 2,063,098; 2,201,956; 2,279,599

## WARRANTY

Complete Warranty Statement at https://buildersbest.com